



Years Warranty*

ANSMANN Desktop Charger DC465PD

Compact USB charging solution for the desktop. 65 W USB mains adapter for laptops, smartphones, tablets and other USB devices.

Features

- USB desktop charger with 4 USB-Ports and 65 W
- Flat, compact design
- Intelligent charge controller ensures optimum charging
- Multisafe technology protects both your end-device and the charger
- Ideal for laptop workstations and devices that can be charged or operated via USB
- Input: 110 - 240V AC Wide-range input enables worldwide use
- Voltage range: 5 - 20V DC
- Power: 65 W



Power



Ultra fast charging



Output USB 3.0 & USB Type C



for notebooks & phones



Multisafe Technology



Power Delivery



Quickcharge 3.0 compatible



Article number: 1001-0141
 Product content: Desktop Charger DC465PD, Velcro strap, operating instructions
 Customs tariff number: 85044083900
 Packing Unit: 5 (166 × 106 × 208 mm)



Specifications

Output voltage	5 - 20V DC			
Input voltage	110 - 240V AC			
Max. output current	3,25 A			
Max. input current	1.5 A			
Charging currents	Mode	Voltage	Current	Power
	USB-C1	5,0 V	3,0 A	15,0 W
	USB-C1	9,0 V	3,0 A	27,0 W
	USB-C1	12,0 V	3,0 A	36,0 W
	USB-C1	15,0 V	3,0 A	45,0 W
	USB-C1	20,0 V	3,3 A	65,0 W
	USB-C2	5,0 V	3,0 A	15,0 W
	USB-C2	9,0 V	2,0 A	18,0 W
	USB-C2	12,0 V	1,5 A	18,0 W
	USB-A1	5,0 V	3,0 A	15,0 W
	USB-A1	9,0 V	2,0 A	18,0 W
	USB-A1	12,0 V	1,5 A	18,0 W
	USB-A2	5,0 V	3,0 A	15,0 W
	USB-A2	9,0 V	2,0 A	18,0 W
	USB-A2	12,0 V	1,5 A	18,0 W
	USB-C1 & C2: C1	5,0 V	3,0 A	15,0 W
	USB-C1 & C2: C1	9,0 V	3,0 A	27,0 W
	USB-C1 & C2: C1	12,0 V	2,5 A	30,0 W
	USB-C1 & C2: C1	15,0 V	2,0 A	30,0 W
	USB-C1 & C2: C1	20,0 V	1,5 A	30,0 W

	Mode	Voltage	Current	Power
	USB-C1 & C2: C2	5,0 V	3,0 A	15,0 W
	USB-C1 & C2: C2	9,0 V	2,0 A	18,0 W
	USB-C1 & C2: C2	12,0 V	1,5 A	18,0 W
	USB-C1 & C2 & A1/A2: C1	5,0 V	3,0 A	15,0 W
	USB-C1 & C2 & A1/A2: C1	9,0 V	3,0 A	27,0 W
	USB-C1 & C2 & A1/A2: C1	12,0 V	2,5 A	30,0 W
	USB-C1 & C2 & A1/A2: C1	15,0 V	2,0 A	30,0 W
	USB-C1 & C2 & A1/A2: C1	20,0 V	1,5 A	30,0 W
	USB-C1 & C2 & A1/A2: C2/A1/A2 shared	5,0 V	3,0 A	15,0 W
USB-Ports	4			
Port	USB-A / USB type C			
Maximum power	65 W			
Average operational efficiency	83,7 %			
Efficiency at low load	73,9 %			
Power consumption at no load	0,200 W			
Charging protocol	Power Delivery Profile 3 / Quick Charge 3.0			
Color	black			
Packaging	cardboard box			
Operating temperature	-20 - 25 °C			
Storage temperature	-25 - 75 °C			