



Years Warranty\*

## ANSMANN Future T400FR

High-quality, rechargeable torch with focussing and water-protected housing for professional use.

### Features

- High-quality, rechargeable aluminium torch for professional use
- Latest high-performance LEDs
- Seamless focussing by turning the lamp head, from a precise point of light to homogeneous floodlighting
- Large on/off switch and non-slip exterior for maximum user comfort even when wearing gloves, ideal for single-handed use
- Four lighting functions: 100% / 30% lighting power, strobe and SOS functions
- Brightness: 400 lumens (100%), 130 Lumens (30%)
- Battery life ca. 3 h (100%), ca. 9 h (30%)
- Lighting range: up to 175 m
- Protection rating: IPX4 / impact-resistant up to 1m drop height
- Including replaceable 18650 Li-Ion rechargeable battery pack, micro-USB cable and wrist strap
- Packaged in an attractive, hanging folded box with viewing window
- 3 year ANSMANN-Germany manufacturer's guarantee



High Power LED



Luminous flux



Brightness



Beam



Operating time



Seamless optic zoom



Rechargeable Li-Ion battery



Aluminium housing



Article number: 1600-0150  
 Product content: Torch, Micro-USB cable, ANSMANN 18650 3.6V Li-Ion rechargeable battery pack, wrist strap  
 Customs tariff number: 8513100000  
 VE Stück: 1



### Specifications

<b>Illuminant</b>	LED				
<b>Illuminant power</b>	10 W				
<b>Light range</b>	175 m				
<b>Luminous flux</b>	400 lumens				
<b>Brightness</b>	7.500 Lux				
<b>Protection class</b>	IPX4				
<b>Operating time</b>	9 h				
<b>Power supply</b>	Li-ion 3.6V 2600mAh with safety electronics				
<b>Light modes</b>	100% lighting power / 30% lighting power / strobe function / SOS function				
<b>Performance data</b>	<b>Mode</b>	<b>Light range</b>	<b>Luminous flux</b>	<b>Brightness</b>	<b>Operating time</b>
	2%	22 m	20 lumens	130 Lux	95 h
	25%	84 m	250 lumens	1.800 Lux	6 h
	100%	184 m	1.000 lumens	8.500 Lux	3 h
<b>Housing material</b>	Aluminium				
<b>Color</b>	black				
<b>Packaging</b>	blister packaging				
<b>Operating temperature</b>	-20 - 25 °C				
<b>Storage temperature</b>	-20 - 20 °C				