



Years Warranty\*

## ANSMANN M350F

Professional 5W LED torch with seamless and infinite focussing, incl. 4x ANSMANN alkaline AAA batteries, removable retaining clip and wrist strap

### Features

- High-quality aluminium torch for professional use
- Uses the latest 5W LED technology from CREE
- Optical zoom: Seamless and infinite focussing from a precise point of light to homogeneous floodlighting by turning the lamp head
- Microcontroller-managed tactical end-cap switch with four lighting functions: Boost/100%/30%/strobe and Morse function
- Non-slip exterior for maximum user comfort even when wearing gloves, ideal for single-handed use
- Brightness: 320 lumen (Boost), 200 lumen (100%), 60 lumen (30%)
- Battery life ca. 1,5h (Boost), ca. 4h (100%), ca. 12h (30%)
- Light range: Up to 140 m
- Protection: IP54 / impact resistance up to 1m drop height
- Includes 4x AAA alkaline batteries, removable belt clip and wrist strap
- Packaged in appealing hanging blister pack
- 3 year ANSMANN-Germany manufacturer's guarantee



High Power LED



Luminous flux



Brightness



Beam



Operating time



Seamless optic zoom



Splashproof



Aluminium housing



Article number: 1600-0172  
 Product content: Torch M350F, 4x Micro AAA batteries, lanyard, belt clip  
 Customs tariff number: 8513100000  
 Packing Unit: 6 (285 × 135 × 285 mm)



### Specifications

<b>Illuminant</b>	LED				
<b>Illuminant power</b>	5 W				
<b>Light range</b>	140 m				
<b>Luminous flux</b>	320 lumens				
<b>Brightness</b>	4.600 Lux				
<b>Protection class</b>	IP54				
<b>Operating time</b>	12 h				
<b>Power supply</b>	3× Micro AAA / LR03				
<b>Light modes</b>	100% / Boost / 30% / Strobe				
<b>Performance data</b>	<b>Mode</b>	<b>Light range</b>	<b>Luminous flux</b>	<b>Brightness</b>	<b>Operating time</b>
	100%	105 m	200 lumens	2.700 Lux	4 h
	Boost	140 m	320 lumens	4.600 Lux	1,5 h
	30%	60 m	60 lumens	920 Lux	12 h
<b>Housing material</b>	Aluminium				
<b>Color</b>	black				
<b>Packaging</b>	blister packaging				
<b>Operating temperature</b>	-10 - 25 °C				
<b>Storage temperature</b>	-10 - 50 °C				