



Years Warranty*

ANSMANN T600FRB

Professional torch – operation with AAA batteries or 18650 li-ion rechargeable batteries – with seamless focussing, incl. 3× ANSMANN alkaline AAA batteries and belt clip

Features

- High-quality aluminium torch for professional use – protection rating: IPX4
- Replaceable energy source: The light can be used with either alkaline batteries or with an 18650 li-ion rechargeable battery – a suitable cartridge for the li-ion rechargeable battery is included.
- We recommend using an ANSMANN 18650 li-ion rechargeable battery with safety circuitry and extended positive terminal.
- Seamless focussing by turning the lamp head – from a precise point of light to homogeneous floodlighting
- Large on/off switch and non-slip exterior for maximum user comfort even when wearing gloves, ideal for single-handed use
- Five lighting functions: 100% / 25% / 10% / Strobe / SOS
- Brightness: 620 lumen (100%), 260 lumen (25%) / 70 lumen (10%) with a lighting range of up to 165 m
- Includes 3× AAA alkaline batteries and belt clip
- 3 year ANSMANN-Germany manufacturer's guarantee

**Luminous flux****Brightness****Beam****Operating time****Rechargeable Li-ion battery****Seamless optic zoom****Aluminium housing****Batteries included**



Article number: 1600-0268
 Product content: T600FRB, 3× AAA batteries, belt clip, operating instructions
 Customs tariff number: 8513100000
 Packing Unit: 5 (281 × 134 × 212 mm)



Specifications

Illuminant	LED				
Illuminant power	10 W				
Light range	165 m				
Luminous flux	620 lumens				
Brightness	6.500 Lux				
Protection class	IPX4				
Operating time	27 h				
Power supply	3× Micro AAA / LR03				
Light modes	100% / 25% / 10% / Strobe / SOS				
Performance data	Mode	Light range	Luminous flux	Brightness	Operating time
	100% / 18650	165 m	620 lumens	6.500 Lux	3 h
	100% / Micro AAA	100 m	360 lumens	2.400 Lux	4 h
	25% / 18650	100 m	260 lumens	2.400 Lux	4,75 h
	25% / Micro AAA	70 m	140 lumens	1.200 Lux	7,5 h
	10% / 18650	50 m	70 lumens	700 Lux	20 h
	10% / Micro AAA	40 m	40 lumens	360 Lux	27 h
Housing material	Aluminium				
Color	black				
Packaging	blister packaging				
Operating temperature	0 - 25 °C				
Storage temperature	-10 - 50 °C				