



ANSMANN WL1500R Pocket Flex

Robust rechargeable work light with additional flexible light arm

Features

- Robust housing with IP65 and IK08 protection
- Flexible, 30cm long, light arm
- Including Hanging hooks and holding magnets
- Light colour main light 6000K and auxiliary light 7000K
- Colour rendering index CRI: Ra > 80
- Luminous flux max. 1,600 lumen, light range up to 100 m
- Battery life up to 16 hours, charge time ca. 3.5 hours
- Power supply Li-Ion rechargeable battery pack with 3.7V | 4.400mAh | 16.28Wh

▪ Packing in cardboard box				
▪ Performance data:				
	Maximum	Maximum	Maximum	Maximum
Mode	light	luminous	brightness	operating
	range	flux		time
Spot	100 m	350	2.200 Lux	12 hrs.
beam		lumens		
25%	15 m	380	700 Lux	16 hrs.
		lumens		
50%	30 m	800	1.500 Lux	7,5 hrs.
		lumens		
100%	50 m	1.600	3.000 Lux	3,5 hrs.
		lumens		



SMD-LED



High Power LED



Luminous flux



Brightness



Operating time



Magnetic mounting



Splashproof



Shock resistance



Article number: 1600-0565

Product content: Lamp, USB-C charge cable, operating instructions



Specifications

Nominal voltage	3,7 V				
Nominal capacity	4400 mAh				
Illuminant	15W + 3W LED				
Illuminant power	15 W				
Maximum light range	100 m				
Maximum luminous flux	1.600 lumens				
Maximum brightness	3.000 Lux				
Protection class	IP65 nur bei Akkubetrieb, IP20 beim Laden				
Maximum operating time	16 hrs.				
Power supply	Li-ion 3.7V 4400mAh 16.28Wh				
Light modes	Leuchtarm / 25% / 50% / 100%				
Performance data	Mode	Maximum light range	Maximum luminous flux	Maximum brightness	Maximum operating time
	Spot beam	100 m	350 lumens	2.200 Lux	12 hrs.
	25%	15 m	380 lumens	700 Lux	16 hrs.
	50%	30 m	800 lumens	1.500 Lux	7,5 hrs.
	100%	50 m	1.600 lumens	3.000 Lux	3,5 hrs.
IK Protection Class	IK08				
Colour temperature	6000 - 7000 K				
Housing material	Aluminium, Nylon, TPR				
Color	black / blue				

Packaging	cardboard box
Operating temperature	-10 - 40 °C
Storage temperature	0 - 30 °C
Dimensions	171 × 76.5 × 40.7 mm