



## ANSMANN Worklight WL1500R Pocket Flex

Robust rechargeable work light with additional flexible light arm

### Features

- Robust housing with IP65 and IK08 protection
- Flexible, 30cm long, light arm
- Including Hanging hooks and holding magnets
- Light colour main light 6000K and auxiliary light 7000K
- Colour rendering index CRI: Ra > 80
- Luminous flux max. 1,600 lumen, light range up to 100 m
- Battery life up to 16 hours, charge time ca. 3.5 hours
- Power supply Li-Ion rechargeable battery pack with 3.7V | 4.400mAh | 16.28Wh
- Packing in cardboard box
- Performance data:

Mode	Light range	Luminous flux	Brightness	Operating time
Spot beam	100 m	350 lumens	2.200 Lux	12 h
25%	15 m	380 lumens	700 Lux	16 h
50%	30 m	800 lumens	1.500 Lux	7,5 h
100%	50 m	1.600 lumens	3.000 Lux	3,5 h



COB-LED



Luminous flux



Protected against water jets



Shock resistance



Magnetic mounting



Hanging Hook



Input USB Type C



Rechargeable Li-Ion battery



Article number: 1600-0565  
 Product content: Lamp, USB-C charge cable, operating instructions  
 Customs tariff number: 8513100000  
 Packing Unit: 20 (370 × 235 × 275 mm)



### Specifications

Nominal voltage	3,7 V				
Nominal capacity	4400 mAh				
Illuminant	15W + 3W LED				
Illuminant power	15 W				
Light range	100 m				
Luminous flux	1.600 lumens				
Brightness	3.000 Lux				
Protection class	IP65 nur bei Akkubetrieb, IP20 beim Laden				
Operating time	16 h				
Power supply	Li-ion 3.7V   4400mAh   16.28Wh				
Light modes	Leuchtarm / 25% / 50% / 100%				
Performance data	<b>Mode</b>	<b>Light range</b>	<b>Luminous flux</b>	<b>Brightness</b>	<b>Operating time</b>
	Spot beam	100 m	350 lumens	2.200 Lux	12 h
	25%	15 m	380 lumens	700 Lux	16 h
	50%	30 m	800 lumens	1.500 Lux	7,5 h
	100%	50 m	1.600 lumens	3.000 Lux	3,5 h
IK Protection Class	IK08				
Colour temperature	6000 - 7000 K				
Housing material	Aluminium, Nylon, TPR				
Color	black / blue				
Packaging	cardboard box				

---

Operating temperature	-10 - 40 °C
Storage temperature	0 - 30 °C

---